



HARTBEN SV 100

TYPE	Aromatic polyisocyanurate.			
DELIVERY FORM	50% in BUTYLACETATE			
COMPOSITION AND PHYSICAL CONSTANTS				
Standard Inspection			Review 000	
		Test Methods	Units	Specifications
PRODUCT SPECIFICATIONS*	BN1	Solids % (+/-1)		50
	BN 5/ASTM D 1544	Colour Gardner - Hellige		2 max.
	BN 6/ASTM D 1545	Viscosity (Gardner-Holdt at 25°C)		T-V
	BN 16/ASTM 2172-91	NCO percentage		7,8-8,2
	BN 20/Visual	Aspect		Clear
PERFORMANCE AND SUGGESTED USES	HARTBEN SV 100 is a high reactive aromatic polyisocyanurate. HARTBEN SV 100 is suggested for producing very fast-curing, easy sandable sealers and topcoats, to be plastycized by adding HARTBEN 75 P, when a better flexibility or build-up are requested.			
SOLUBILITY AND COMPATIBILITY	Aromatics Aliphatics Esters-Ketones	Limited Insoluble Soluble		
STORAGE AND SHELF LIFE	The resin should be stored indoors in the original, unopened and undamaged containers in a dry place at storage temperatures between 5°C and 30°C. Exposure to direct sunlight should be avoided.			
GUIDELINE AND SAFETY	Under the above mentioned storage conditions the shelf life of the resin will be at least 12 months ex works. For any information related to handling and toxicological knowledge about this resin please refer to the Safety data Sheet.			
*Product Specification Hartben SV 100				
Review 000				
Customer Approval Signature:		Date:		
(Nothing receiving within 7 days, we assume accepted the conditions we proposed.)				

This edition deletes and substitutes all the preceeding ones. The above information is reliable and accurate to the best of our knowledge and is not intended to violate any existing or pending patents.
We suggest always to carry out laboratory tests before using the product.